

**IN THE CLAIMS:**

The text of all pending claims, (including withdrawn claims) is set forth below. Cancelled and not entered claims are indicated with claim number and status only. The claims as listed below show added text with underlining and deleted text with ~~strikethrough~~. The status of each claim is indicated with one of (original), (currently amended), (cancelled), (withdrawn), (new), (previously presented), or (not entered). Please AMEND claims \* and ADD new claims \* in accordance with the following:

1. (PREVIOUSLY AMENDED) A flat display unit comprising:  
a display panel;  
a circuit board having circuits thereon for driving the display panel; and  
a chassis combining the display panel and the circuit board into a unit, said chassis having first and second surfaces opposite to each other on which the display panel and the circuit board are mounted, respectively, and a side wall extending from an edge of the first surface on which the display panel is mounted, perpendicularly to the first surface, and along the periphery of the display panel.
2. (ORIGINAL) A flat display unit as set forth in claim 1, wherein said chassis further comprises another side wall extending from the edge of the second surface on which the circuit board is mounted, perpendicularly to the second surface, and covering the periphery of the circuit board.
3. (PREVIOUSLY AMENDED) A flat display unit as set forth in claim 1, wherein said chassis includes fins provided on the second surface the circuit board is mounted thereon, in the form of a plurality of protrusions.
4. (PREVIOUSLY AMENDED) A flat display unit as set forth in claim 1, wherein said chassis has a through-hole formed adjacent to the periphery thereof, the through-hole allowing a cable to pass therethrough for electrically interconnecting the display panel and the circuit board.
5. (PREVIOUSLY AMENDED) A flat display unit as set forth in claim 1, wherein

said chassis comprises first and second sub-chassis on which the display panel and the circuit board are mounted, respectively, wherein the first and second sub-chassis are joined together through respective rear surfaces thereof.

6. (PREVIOUSLY AMENDED) A flat display unit as set forth in claim 1, wherein said chassis has a cut-out formed at a side thereof, the cut-out allowing a cable to pass therethrough for electrically interconnecting the display panel and the circuit board.

7. (PREVIOUSLY AMENDED) A flat display unit including a chassis mounted with a display panel and a circuit board for driving the display panel, on both surfaces thereof, respectively, for combining the display panel and the circuit board into a unit, wherein the chassis comprises a pair of recesses provided in both of the surfaces, respectively, and the display panel is adhered to one of the recesses by an adhesive and the circuit board is secured to another of the recesses by a securing element or material, and wherein the display panel and the circuit board are electrically interconnected with each other by a wiring cable which is lead to both of the surfaces of the chassis through a through-hole provided in the chassis.

8. (PREVIOUSLY AMENDED) A method for fabricating a flat display unit in which a display panel and a circuit board for driving the display panel are combined into a unit through a chassis, the method comprising :

connecting each of terminals at an end of a flexible cable to corresponding one of a plurality of electrode terminals exposed on an edge of the display panel;

preparing a chassis having front and rear surfaces opposite to each other, a side wall extending from the periphery of the chassis, perpendicularly to the front surface, and a recess defined on the front surface by the side wall ;

accommodating the display panel in the recess and adhering thereto the display panel;

extending another end of the flexible cable to the rear surface of the chassis through a through-hole provided in the chassis;

mounting the circuit board on the rear surface of the chassis;

connecting said another end of the flexible cable to the circuit board, so that the circuit board and the display panel are in a mutually conductive condition.

9. (PREVIOUSLY AMENDED) A method for fabricating a flat display apparatus in

which a display panel and a circuit board for driving the display panel are combined into a unit through a chassis, the method comprising :

connecting each of terminals at an end of a flexible cable to corresponding one of plurality of electrode terminals exposed on an edge of the display panel;

preparing a first chassis having front and rear surfaces opposite to each other, a side wall which extends from the periphery of the first chassis, perpendicularly to the front surface, and a recess defined on the front surface by the side wall surrounding thereof;

accommodating the display panel in the recess and adhering thereto the display panel;

extending another end of the flexible cable to the rear surface of the first chassis through a through-hole provided in the first chassis;

mounting the circuit board on a front surface of a second chassis having a rear surface opposite to the front surface thereof;

passing said another end of the flexible cable through a through-hole provided in the second chassis so as to extend to the front surface of the second chassis;

adhering respective said rear surfaces of the first and second chassis;

connecting said another end of the flexible cable to the circuit board, so that the circuit board and the display panel are in a mutually conductive condition.

10. (ORIGINAL) A method for fabricating a flat display apparatus as set forth in claim 8, wherein the chassis further comprises a cut-out provided on an edge thereof, and the circuit board and display panel are connected each other by the flexible cable passing through the cut-out.

11. (ORIGINAL) A method for fabricating a flat display apparatus as set forth in claim 9, wherein each of the first and second chassis further comprises a cut-out provided on a respective corresponding one of edges thereof, and the circuit board and display panel are connected each other by the flexible cable passing through the cut-out.

12. (CURRENTLY AMENDED) ~~A chassis to be used in a flat display unit, wherein a display panel and a circuit board are respectively mounted on a pair of opposite surfaces of the chassis and combined into a unit, and wherein the chassis comprises a side wall extending from the periphery thereof, perpendicularly to one of the surfaces, on which the display panel is mounted, comprising:~~

a support structure having first and second opposite main surfaces affording mounting thereon, and support of, a display panel and a circuit board to drive the display panel, together forming a display unit; and

the support structure further comprising a sidewall extending perpendicularly from the first surface, on which the display panel is to be mounted, adjacent a periphery of the support structure and spaced from but extending along a periphery of the display panel to be mounted on the first surface.

13. (CURRENTLY AMENDED) A chassis as set forth in claim 12, wherein the chassis further comprises a through-hole connecting the ~~pair of~~ first and second opposite surfaces on which the display panel and the circuit board are respectively to be mounted and affording a passageway for passage therethrough of a flexible cable to electrically connect the display panel and the circuit board ~~are electrically connected by a flexible cable passing through the through-hole.~~

14. (ORIGINAL) A flat display unit as set forth in claim 2, wherein said chassis includes fins provided on the second surface of the circuit board is mounted thereon, in the form of a plurality of protrusions.

15. (ORIGINAL) A flat display unit as set forth in claim 2, wherein said chassis has a through-hole formed adjacent to the periphery thereof, the through-hole allowing a cable to pass therethrough for electrically interconnecting the display panel and the circuit board.

16. (ORIGINAL) A flat display unit as set forth in claim 2, wherein said chassis comprises first and second sub-chassis on which the display panel and the circuit board are mounted, respectively, wherein the first and second sub-chassis are joined together through respective rear surfaces thereof.

17. (ORIGINAL) A flat display unit as set forth in claim 2, wherein said chassis has a cut-out formed at a side thereof, the cut-out allowing a cable to pass therethrough for electrically interconnecting the display pane and the circuit board.

18. (ORIGINAL) A flat display unit as set forth in claim 1, wherein the side wall

extends along and covers the periphery of the display panel.

19. (ORIGINAL) A flat display unit as set forth in claim 1, wherein the side wall extends along and covers the entire periphery of the display panel.

20. (NEW) A chassis as recited in claim 12, wherein:  
the sidewall defines a first recess in which the display panel is received, when mounted on the first surface of the support structure.

21. (NEW) A chassis as recited claim 12, wherein the sidewall extends perpendicularly to the second main surface of the support so as to define, with the second main surface, a second recess in which the circuit board is received, when mounted on the second surface of the support structure.

22. (NEW) A chassis as recited in claim 12, wherein the display panel is of a thickness of a first dimension and the sidewall extends from the first main surface by a distance greater than the first dimension.

23. (NEW) A chassis as recited in claim 12, wherein the circuit board is of a thickness of a second dimension and the sidewall extends from the second surface by a distance which is greater than the second dimension.